

Quality Wood Finishing Products



CATALYZED VARNISH

EXTREMELY LOW ODOR * ULTRA LOW HAPS * EXTENDED POT LIFE * WATER WHITE

PRODUCT DESCRIPTION

WOODWRIGHT E7 IS A HIGH BUILD, MODIFIED COCONUT ALKYD CATALYZED VARNISH WITH ATTRACTIVE GRAIN ENHANCING CHARACTERISTICS. IT HAS EXTREMELY LOW ODOR AND MINIMAL EYE & NOSE IRRITATION. THIS PRODUCT CONTAINS LOW HAPS AND VERY LOW VOC. E7 IS A TRUE HIGH END PERFORMANCE COATING WITH EXCELLENT RESISTANCE TO SCRATCHING, MARRING, MOISTURE AND CHEMICALS. E7 PROVIDES A GREAT VALUE BY BEING COMPETITIVELEY PRICED AND HAVING AN EXTENDED POT-LIFE (WHICH YIELDS VIRTUALLY NO WASTE). THE RESINS SELECTED FOR THIS PRODUCT PROVIDE A CLEAR, WATER WHITE FINISH. AS WITH ALL WOODWRIGHT FINISHES, THIS VARNISH HAS A SILKY FEEL ADDING TO YOUR FURNITURE OR CABINETRY'S QUALITY. E7 REQUIRES ONLY 4OZ. OF CATALYST PER GALLON AND IS AT A VISCOSITY THAT IS READY TO SPRAY FROM THE CAN. THIS PROVIDES EASE OF APPLICATION AND NO LOSS OF SOLIDS DUE TO THINNING OR A HIGH RATIO OF CATALYST. E7 CAN BE USED OVER ANY WOODWRIGHT CATALYZED SEALER BUT CAN BE USED AS A SELF-SEAL PRODUCT, AS WELL.

PHYSICAL PROPERTIES

TYPE: MODIFIED COCONUT ALKYD AIR DRY SCHEDULE W/ 40Z. CATALYST PER GALLON:

 V.O.C.:
 4.24 LB/GAL. (NO H20)
 TO TOUCH:
 20-30 MINUTES

 WEIGHT/GAL.:
 7.9 LB + OR – 0.15
 TO SAND:
 60 MINUTES

 VISCOSITY:
 24.50-25.50 SEC. ZAHN #2 EZ @ 77 F.
 TO RECOAT:
 60 MINUTES

SHEENS: 5, 20, 35, 45, 60, 90 **TO PACK:** 8 HOURS

WEIGHT SOLIDS: 37% + OR – 1% **VOLUME SOLIDS:** 32% + OR – 1%

APPLICATION

METHOD: SPRAY, AIRLESS OR AIR ASSISTED (STAINLESS STEEL EQUIPMENT REQUIRED)

REDUCER: WOODWRIGHT TH2910 LACQUER THINNER OR TH7100 FLOSOL, IF DESIRED

SUBSTRATE: WOOD (STAINED IF DESIRED), CLEAN AND DUST FREE
CATALYST: WOODWRIGHT 35260 CATALYST (4OZ. PER GALLON)
POT LIFE: UP TO 48 HOURS @ 77 DEG. F. (SEALED AIRTIGHT)

SHELF LIFE: 1YEAR (UNOPENED)

