

Quality Wood Finishing Products



LOW ODOR · LOW HAPS · EXTENDED POT LIFE

PRODUCT DESCRIPTION

WOODWRIGHT E7 ADVANCE SEALER IS A HIGH BUILD, NON-YELLOWING, COCONUT ALKYD CATALYZED SEALER WITH FAST DRY AND EXCEPTIONAL SANDABILITY. IT HAS AN EXTREMELY LOW ODOR AND HAPS CONTENT. 9935 SEALER IS A TRUE HIGH END PERFORMANCE SEALER. COMPETITIVELEY PRICED, WITH AN EXTENDED POT-LIFE (WHICH YEILDS VIRTUALLY NO WASTE), 9935 SEALER PROVIDES A GREAT VALUE. THE RESINS SELECTED FOR THIS PRODUCT PROVIDE AN EXTREMELY CLEAR, NON-YELLOWING FILM MAKING IT IDEAL FOR USE IN WHITE FINISH SYSTEMS. E7 ADVANCE SEALER REQUIRES ONLY 40Z. OF CATALYST PER GALLON AND IS AT A VISCOSITY THAT IS READY TO SPRAY FROM THE CAN, PROVIDING EASY APPLICATION AND NO LOSS OF SOLIDS DUE TO THINNING OR A HIGH RATIO OF CATALYST.

PHYSICAL PROPERTIES

TYPE: MODIFIED COCONUT ALKYD AIR DRY SCHEDULE W/ 4OZ. CATALYST PER GALLON:

V.O.C.: 4.44 LB/GAL. (NO H20) TO TOUCH: 20-25 MINUTES WEIGHT/GAL.: 7.7 LB + OR - 0.15TO SAND: 45-60 MINUTES VISCOSITY: 26-27 SEC. ZAHN #2 EZ @ 77 F. TO RECOAT: 45-60 MINUTES

32% + OR - 1% **VOLUME SOLIDS:**

APPLICATION

SPRAY, AIRLESS OR AIR ASSISTED (STAINLESS STEEL EQUIPMENT REQUIRED) METHOD: **REDUCER:** WOODWRIGHT TH2910 LACQUER THINNER OR TH7100 FLOSOL, IF DESIRED

SUBSTRATE: WOOD (STAINED IF DESIRED), CLEAN AND DUST FREE

CATALYST: WOODWRIGHT 35260 CATALYST (40Z. PER GALLON) ON WOODWRIGHT STAINS

UP TO 48 HOURS @ 77°F CATALYZED (SEALED AIRTIGHT) POT LIFE:

1YEAR (UNOPENED) SHELF LIFE:

USE 5 OZ 35260 CATALYST PER GALLON WHEN SPRAYING FOR DARK STAINS:

OVER DARK STAINS THAT ARE NOT WOODWRIGHT BRAND